

VAPOR TIGHT SERIES



VP4PB151W120/277V-50K

4 feet - 51 Watts (1x51W)
6 000 lumens - 120/277V
5000K - Beam angle 90° angle

Non-metallic outdoor lighting, available in LED, fade & rust resistant composite construction, wall or ceiling mount, ETL listed for wet locations

Dust and water resistant LED IP66 50W (NEMA 4X), wall or ceiling mount.

Fade & Rust Resistant Composite Construction, 316 SS Tamper Resistant Latches, F1 Rated For Outdoors, Captive Lens Design.

LOW BAY SERIES

IP65 waterproof luminaire can be used for warehouses, parking lots, stairwells and many others.

It can be dimmable, with motion detector and emergency work. It will allow you to make considerable savings both in energy consumption and maintenance costs.

Low Bay 40W, 80W, 100W Led Luminaire.

Extruded aluminum housing with shock-resistant polycarbonate coating. Improve heat dissipation with a flexible installation with a full-length polycarbonate lens, this is a watertight, dustproof and corrosion resistant product. Suggested height for installation is 6'5" to 49'.



LR/PB40W100/277V-50K

2 feet - 40 Watts
6 000 lumens - 120/277V
5000K - Beam angle 120° angle

LR/PB80W100/277V-50K

4 feet - 80 Watts
12 000 lumens - 120/277V
5000K - Beam angle 120° angle

LR/PB100W100/277V-50K

5 feet - 100 Watts
15 000 lumens - 120/277V
5000K - Beam angle 120° angle

LIGHTBOX LED RETRO-FIT



The CBM Lightbox Retro-fit fixture is one of the simplest LED conversions in the industry. Get extended life out of your current fluorescent vapor-tight fixtures. The 46" long Lightbox fixture has the same profile as (2) 4' T-8 fluorescent bulbs mounted in a fixture. With a whopping 14,760 lumens, it will outperform any 2-lamp 8' fluorescent fixture available. No need to replace your current vapor-tight fixtures that are in good working order as the universal Lightbox design allows for it to be installed in a large majority of current vapor-tight fixtures in the industry, this includes 4'-8' fixtures in 2,3,4 and 6-lamp configurations.

The Lightbox retro-fit fixture is easy to install. The Lightbox fixture magnetically connects to the face of the vapor-tight tray. (Stick-on polarized magnets included for non-metallic tray covers) The unique design of the Lightbox fixture allows for an improvement of up to 60% over standard LED conversions in 8-10' ceiling heights. The placement of the LED strips around all four sides, as well as the face of the fixture, allows to direct light horizontally giving optimal 360* lighting performance in a low ceiling environment.

82-Watt Power Usage - 14,760 Lumen Output - 200,000 Hour LED Life, (Over 22 years of 24/7 operation) - 10 Years Standard Warranty, 100% replacement of any defective products - Qualifies for Rebate Programs, (Check with local utility for availability) - Designed for Harsh Industrial Agricultural Environment - High end components keep consistent lighting as feed & ventilation motors cycle on & off - LED light will not change color over time.

Lighting products to answer all your needs

AWC SERIES

IP67 waterproof luminaire with LED boards or LED tubes for farm building, commercial, warehouse and industrial. It will allow you to make considerable savings both in energy consumption and maintenance costs.



AWC/2/PB123W120/277V-50K

2 feet - 23 Watts (1x23W)
4 000 lumens - 120/277V
5000K - Beam angle 120° angle



AWC220LED120/277V-65K

4 feet - 40 Watts (2x18W High lumen)
5 600 lumens - 120/277V
6500K - Beam angle 120° angle

AWC320LED120/277V-65K

4 feet - 60 Watts (3x18W High lumen)
8 400 lumens - 120/277V
6500K - Beam angle 120° angle

WN SERIES

An IP66 waterproof luminaire with LED boards ideal for warehouse.

Structure: anodized 6063 aluminum + polyester fiber reinforced housing, polycarbonate diffuser

WN/6/PB623W120/277V-50K

6 feet - 138 Watts (6x23W)
24 000 lumens - 120/277V
5000K - Beam angle 140° angle



WP SERIES

An IP65 waterproof luminaire with LED tubes can be adjustable or non-adjustable for agricultural, commercial, warehouse and industrial buildings.



WP220LED120/277V-65K

4 feet - 40W (2x18W High lumen)
9 900 lumens - 120/277V
6500K - Beam angle 120° angle

WP320LED120/277V-65K

4 feet - 60W (3x18W High lumen)
6 600 lumens - 120/277V
6500K - Beam angle 120° angle

ACCESSORIES



EC2P ET EC4P

2 OR 4 pin Cables
3', 5' 10', 12' et 15'



EC2PT / EC4PT

T- Cable
2 or 4 pins



STL/MBRK

Stainless steel
mounting brackets



EC2PEND / EC4PEND

Cable plugs



EC2PFP/EC2PMP, EC4PFP/EC4PMP

Cable + pig tail
female or male
2 or 4 pins



EC2PTSOCKET

T- Cable with socket

Lighting products to answer all your needs

OTHER PRODUCTS FOR YOUR BUILDINGS



SCR

Sealed LED light bulb
Dimmable or On/Off
Power 7 and 12 watts



HB LED STRIP

Highbay with LED boards IP67 or IP69
Available in 60 and 120 cm
Power from 92 to 184 watts



SCRJJ

For Led conversion
Sealed LED light bulb
Dimmable or On/Off
Power 7 and 12 watts
2700K, 5000K, Full spectrum



HB LED TUBE

Highbay with IP67 or IP69 LED tubes
Available in 60 and 120 cm



SCRTS

Sealed LED light bulb with T
socket Dimmable or On/Off
Power 7 and 12 watts



PL

Panel Led light
Very uniform light output
No dark areas



TBV / TBL

Linear or V-tube
Dimmable or On/Off



LWP

Waterproof wall Led light IP65



CM

Commercial spot or flood Led
light 240W or 320W treated
against corrosion



EP

Explosion proof Led boards or Led
tubes 4' or 8' IP67
Class I, div. 2 Group: ABCD



SL

IP66 waterproof street light
with LED multi-chips



HB UFO

Round Highbay LED waterproof IP65
Power of 100, 150 and 200 watts